



## Road saws

### For Skidsteers and Compact Track Loaders

Two models offering 0-10" and 0-18" depth capability

Hydraulic depth and sideshift of cutting wheel

**RS18** has with Rotary Power XF10G radial piston motor drive

**RS18** can be equipped with cutting wheel widths of 3", 4.5" and 6"

**RS10** has Sauer 2.68 cu in piston motor / Fairfield 7HBX planetary drive

**RS10** can be equipped with cutting wheel widths of 2.5 and 4.5"



RS10

## Applications:

Asphalt patch cuts

Fiber optic / wi-fi cuts

Water / sewer cuts

Soil trenching

Model	Min GPM / PSI	Cutting Width	Cutting Depth	# Cutting Teeth	Sideshift	Weight
RS10-2.5	27 / 2,750	2.5 inches	0-10 inches	26	26 inches	1,325
RS10-4.5	30 / 2,750	4.5 inches	0-10 inches	34	26 inches	1,450
RS18-3.0	32 / 3,000	3.0 inches	0-18 inches	30	26 inches	2,345
RS18-4.5	32 / 3,000	4.5 inches	0-18 inches	34	26 inches	2,395
RS18-6.0	32 / 3,000	6.0 inches	0-18 inches	60	26 inches	2,455

RoadHog, Inc. • 877-640-9975 • [www.roadhoginc.com](http://www.roadhoginc.com) • [sales@roadhoginc.com](mailto:sales@roadhoginc.com)

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

Rev 5/23