



Road saws

For Skidsteers and Compact Track Loaders

Two models offering 0-10" and 0-18" depth capability

Hydraulic depth and sideshift of cutting wheel

Sauer 2.68 cu in piston motor / Auburn 8S2B planetary (RS18)

Cutting widths of 3", 4.5" and 6" (RS18)

Sauer 2.68 cu in piston motor / Fairfield 7HB planetary (RS10)

Cutting widths of 2.5 and 4.5" (RS10)



RS10

Applications:

Asphalt patch cuts

Fiber optic / wi-fi cuts

Water / sewer cuts

Soil trenching

Model	Min GPM / PSI	Cutting Width	Cutting Depth	# Cutting Teeth	Sideshift	Weight
RS10-2.5	27 /2,750	2.5 inches	0-10 inches	26	26 inches	1,325
RS10-4.5	30/ 2,750	4.5 inches	0-10 inches	34	26 inches	1,450
RS18-3.0	32/3,000	3.0 inches	0-18 inches	30	26 inches	2,345
RS18-4.5	32/3,000	4.5 inches	0-18 inches	34	26 inches	2,395
RS18-6.0	32/3,000	6.0 inches	0-18 inches	60	26 inches	2,455

RoadHog, Inc. • 877-640-9975 • www.roadhoginc.com • sales@roadhog-inc.com

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

Rev 2/20