

RoadHog, Inc.

CP Series
Cold Planers
Skid Steer Model

Hydraulic
Cold Planers:

CP12LF
CP16LF

CP16
CP18
CP24
CP30
CP40
CP48

CP24-HD
CP30-HD
CP40-HD

Hydraulic
Road Saws:

RS10-2.5
RS10-4.5
RS10FC-2.5
RS10FC-4.5

RS18-3.0
RS18-4.5
RS18-6.0

Self Contained
Cold Planers:

RH1850
RH2450
RH2460
RH4060
RH3075
RH4075
RH40140
RH48140
RH60140
RH48200
RH60200
RH72200
RH48275
RH60275
RH72275
RH84275
RH96275



**The most advanced skid steer cold planer available today.
Designed & manufactured by the team that pioneered
cold planer attachments for the skid steer industry.**

**Proven driveline with the industry's best service &
support yields Lowest Cost of Ownership.**



RoadHog, Inc.



Applications:

- ✓ Removal of asphalt surfaces prior to overlay
- ✓ Shoulder widening projects
- ✓ Pothole repair
- ✓ Restoring drainage near curb lines & and catch basins
- ✓ Mixing stabilizing agents into base for a more durable repair

Standard Features & Equipment:

LF Models:

- ✓ Operate on standard flow hydraulics
- ✓ Hydraulic sideshift, manual tilt & depth

G5 Models:

- ✓ Independent depth skis for precise lap cuts
- ✓ Large drum access door for quick & easy tooth inspection
- ✓ Planetary gear drive delivering high torque to cutting drum
- ✓ Hydraulic sideshift, tilt & depth controls for maximum control

HD Models:

- ✓ 1.5-inch drum thickness for longer service life
- ✓ 5-inch tooth tip clearance reducing drag in the cut



Optional Features:

- ✓ 40 gallon gravity feed water system to increase tooth life & reduce dust
- ✓ Job specific drums from 2.5-inches to 36-inches based on chassis size
- ✓ Cutting teeth for various cutting surfaces & depths

Hydraulic Cold Planers:

CP12LF
CP16LF

CP16
CP18
CP24
CP30
CP40
CP48

CP24-HD
CP30-HD
CP40-HD

Hydraulic Road Saws:

RS10-2.5
RS10-4.5
RS10FC-2.5
RS10FC-4.5

RS18-3.0
RS18-4.5
RS18-6.0

Self Contained Cold Planers:

RH1850
RH2450
RH2460
RH4060
RH3075
RH4075
RH40140
RH48140
RH60140
RH48200
RH60200
RH72200
RH48275
RH60275
RH72275
RH84275
RH96275

Model	Cutting Width	Cutting Depth	Tilt	Sideshift	# of Teeth	Min.GPM & PSI Required	Estimated Weight	RHS Wall Clearance
CP12LF	12-inches	0 to 5-inches	+/- 15-degrees	26-inches	30	15 GPM / 2,000 PSI	1,220	
CP16LF	16-inches	0 to 5-inches	+/- 15-degrees	26-inches	38	15 GPM / 2,000 PSI	1,250	
CP16-G5	16-inches	0 to 6-inches	+/- 15-degrees	26-inches	38	24 GPM / 2,000 PSI	1,765	3.97-inches
CP18-G5	18-inches	0 to 6-inches	+/- 15-degrees	26-inches	40	24 GPM / 2,000 PSI	1,805	3.97-inches
CP24-G5	24-inches	0 to 6-inches	+/- 13-degrees	26-inches	50	27 GPM / 2,000 PSI	1,970	3.97-inches
CP30-G5	30-inches	0 to 6-inches	+/- 10-degrees	26-inches	60	30 GPM / 2,500 PSI	2,155	3.97-inches
CP40-G5	40-inches	0 to 6-inches	+/- 8-degrees	26-inches	76	30 GPM / 3,000 PSI	2,450	3.97-inches
CP48-G5	48-inches	0 to 6-inches	+/- 6-degrees	26-inches	90	30 GPM / 3,500 PSI	2,685	3.97-inches
CP24-HD	24-inches	0 to 8-inches	+/- 13-degrees	26-inches	50	27 GPM / 2,000 PSI	2,120	4.86-inches
CP30-HD	30-inches	0 to 8-inches	+/- 10-degrees	26-inches	60	30 GPM / 2,000 PSI	2,770	4.86-inches
CP40-HD	40-inches	0 to 8-inches	+/- 8-degrees	26-inches	76	30 GPM / 2,750 PSI	2,910	4.86-inches

Sold & Serviced by Your Local Dealer: