

RoadHog, Inc.

RH Series
Cold Planers
Self Contained

Hydraulic
Cold Planers:

CP12LF
CP16LF

CP16
CP18
CP24
CP30
CP40
CP48

CP24-HD
CP30-HD
CP40-HD

Hydraulic
Road Saws:

RS10-2.5
RS10-4.5
RS10FC-2.5
RS10FC-4.5

RS18-3.0
RS18-4.5
RS18-6.0

Self Contained
Cold Planers:

RH1850
RH2450
RH2460
RH4060
RH3075
RH4075
RH40140
RH48140
RH60140
RH48200
RH60200
RH72200
RH48275
RH60275
RH72275
RH84275
RH96275

Wheel Loader Model



Designed for cutting asphalt & utility trenches, profiling concrete as well as reclaiming or stabilizing pavement & base materials.

Units are completely self contained & require no hydraulic or electrical power from host vehicle. Wireless remote operation of depth, sideshift & tilt.

Standard equipment includes master control panel, hour meter, shutdown system & hydraulically engaged clutch with optional pressurized water system.



RoadHog, Inc.



Single pass cut prior to utility installation



Controlled depth milling - RH48200



In place pavement recycling - RH40140



Reclamation / Stabilization: RH40140 with Optional Oil Injection System. Injecting asphalt emulsion during stabilization pass 4-inch deep at 25 FPM.



Available in quick-attach or pin-on styles



Optimized tooth pattern with blocks



Full depth reclamation of rural, high traffic road. RH60200 pictured with optional 80 gallon pressurized water system.

Hydraulic Cold Planers:

- CP12LF
- CP16LF

- CP16
- CP18
- CP24
- CP30
- CP40
- CP48

- CP24-HD
- CP30-HD
- CP40-HD

Hydraulic Road Saws:

- RS10-2.5
- RS10-4.5
- RS10FC-2.5
- RS10FC-4.5

- RS18-3.0
- RS18-4.5
- RS18-6.0

Self Contained Cold Planers:

- RH1850
- RH2450
- RH2460
- RH4060
- RH3075
- RH4075
- RH40140
- RH48140
- RH60140
- RH48200
- RH60200
- RH72200
- RH48275
- RH60275
- RH72275
- RH84275
- RH96275

Model	Engine HP	Cutting Width	Cutting Depth	# Cutting Teeth	Tilt	Sideshift	Weight*
RH40140	Deere 140 HP Cat 138 HP	40-inches	0 to 12-inches	104	+/- 5 deg.	30-inches	10,100
RH48140	Deere 140 HP Cat 138 HP	48-inches	0 to 12-inches	118	+/- 5 deg.	30-inches	10,650
RH60140	Deere 140 HP Cat 138 HP	60-inches	0 to 12-inches	144	+/- 5 deg.	30-inches	11,250
RH48200	Deere 200 HP Cat 202 HP	48-inches	0 to 12-inches	118	+/- 5 deg.	30-inches	11,300
RH60200	Deere 200 HP Cat 202 HP	60-inches	0 to 12-inches	144	+/- 5 deg.	30-inches	11,750
RH72200	Deere 200 HP Cat 202 HP	72-inches	0 to 12-inches	159	NA	24-inches	12,450
RH48275	Deere or Cat 275 HP	48-inches	0 to 12-inches	118	+/- 5 deg.	30-inches	11,750
RH60275	Deere or Cat 275 HP	60-inches	0 to 12-inches	144	+/- 5 deg.	30-inches	12,200
RH72275	Deere or Cat 275 HP	72-inches	0 to 12-inches	159	NA	24-inches	12,900
RH84275	Deere or Cat 275 HP	84-inches	0 to 12-inches	185	NA	NA	13,600
RH96275	Deere or Cat 275 HP	96-inches	0 to 12-inches	209	NA	NA	14,300