



## Cold Planers

### For Skidsteers and Compact Track Loaders

18, 24", 30", 40" and 48" cutting width; 0-6" cutting depth

Independent control of left and right replaceable depth skis

Electro-hydraulic tilt, depth and sideshift of cutting drum position

Sauer 2.68 cu in M44 piston motor / 24:1 Fairfield planetary drive hub

Optional 40 gallon ROPS mounted gravity fed water system

Optional drum widths to fit any job requirement



## Applications:

Milling asphalt prior to overlay

Cutting utility trenches

Base material reclamation

Pothole and shoulder repair

Restoring drainage elevation against curb lines

Removing trip hazards

Model	Min GPM / PSI	Cutting Width	Cutting Depth	# Cutting Teeth	Tilt	Sideshift	Weight
CP18G5	27 / 2,750	18 inches	0-6 inches	40	+/- 15 deg.	26 inches	1,805
CP24G5	30 / 2,750	24 inches	0-6 inches	56	+/- 13 deg.	26 inches	1,970
CP30G5	34 / 3,000	30 inches	0-6 inches	66	+/- 10 deg.	26 inches	2,155
CP40G5	37 / 3,450	40 inches	0-6 inches	76	+/- 8 deg.	26 inches	2,450
CP48G5	40 / 3,450	48 inches	0-6 inches	90	+/- 6 deg.	26 inches	2,685

RoadHog, Inc. • 877-640-9975 • [www.roadhoginc.com](http://www.roadhoginc.com) • [sales@roadhog-inc.com](mailto:sales@roadhog-inc.com)

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

Rev 2/20