



## Cold Planers

### For Skidsteers and Compact Track Loaders

18, 24", 30", 40" and 48" cutting width; 0-8" cutting depth

1.5" drum wall for added weight, 5 inch tooth clearance provides less drag

Independent control of left and right replaceable depth skis

Electro-hydraulic tilt, depth and sideshift of cutting drum position

Sauer 2.68 cu in M44 piston motor / 24:1 Fairfield planetary drive system



## Applications:

Milling asphalt prior to overlay

Cutting utility trenches

Base material reclamation

Pothole and shoulder repair

Restoring drainage elevation against curb lines

Small stabilization jobs

| Model    | Min GPM / PSI | Cutting Width | Cutting Depth | # Cutting Teeth | Tilt        | Sideshift | Weight |
|----------|---------------|---------------|---------------|-----------------|-------------|-----------|--------|
| CP18G5HD | 27 / 2,750    | 18 inches     | 0-8 inches    | 46              | +/- 15 deg. | 26 inches | 1,990  |
| CP24G5HD | 30 / 2,750    | 24 inches     | 0-8 inches    | 56              | +/- 13 deg. | 26 inches | 2,120  |
| CP30G5HD | 32 / 3,000    | 30 inches     | 0-8 inches    | 66              | +/- 10 deg. | 26 inches | 2,770  |
| CP40G5HD | 32 / 3,250    | 40 inches     | 0-8 inches    | 76              | +/- 8 deg.  | 26 inches | 2,910  |
| CP48G5HD | 35 / 3,250    | 48 inches     | 0-8 inches    | 90              | +/- 6 deg.  | 26 inches | 3,165  |

RoadHog, Inc. • 877-640-9975 • [www.roadhoginc.com](http://www.roadhoginc.com) • [sales@roadhog-inc.com](mailto:sales@roadhog-inc.com)

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

Rev 8/20