



Cold Planers

For Skidsteers and Compact Track Loaders

18, 24", 30", 40" and 48" cutting width; 0-8" cutting depth

1.5" drum wall for added weight, 5 inch tooth clearance provides less drag

Independent control of left and right replaceable depth skis

Electro-hydraulic tilt, depth and sideshift of cutting drum position

Sauer 2.68 cu in M44 piston motor / 24:1 Fairfield planetary drive system



Applications:

Milling asphalt prior to overlay

Cutting utility trenches

Base material reclamation

Pothole and shoulder repair

Restoring drainage elevation against curb lines

Small stabilization jobs

Model	Min GPM / PSI	Cutting Width	Cutting Depth	# Cutting Teeth	Tilt	Sideshift	Weight
CP18G5HD	30/3,000	18 inches	0-8 inches	46	+/- 15 deg.	26 inches	1,990
CP24G5HD	30/ 3,000	24 inches	0-8 inches	56	+/- 13 deg.	26 inches	2,350
CP30G5HD	32/3,250	30 inches	0-8 inches	66	+/- 10 deg.	26 inches	2,770
CP40G5HD	32/ 3,250	40 inches	0-8 inches	76	+/- 8 deg.	26 inches	2,910
CP48G5HD	35/ 3,250	48 inches	0-8 inches	106	+/- 6 deg.	26 inches	3,205

RoadHog, Inc. • 877-640-9975 • www.roadhoginc.com • sales@roadhog-inc.com

Specifications and designs are subject to change without notice. Machines may be shown with optional equipment.

Rev 9/20